

*CLAIM AMENDMENTS*

Rewrite claims 1, 12, 13, 16, 17 and 18 as follows:

1. (Currently Amended) A window shade for motor vehicles comprising:  
a winding shaft to which an edge of a shade web is fastened,  
a pull rod arrangement attached to the shade web at a location which is remote from  
where the shade web is connected to the winding shaft for movement with the window shade  
web between open and closed positions,  
at least one guide rail for guiding movement of the pull rod arrangement, and  
~~at least one elastic lip which extends mounted along the guide rail in contacting~~  
~~elastically deformed relation to the pull rod arrangement for biasing and maintaining the pull~~  
~~rod arrangement into continuous rattle-free contact with the guide rail, and is positioned in~~  
~~such a way that it is in contact with the pull rod arrangement and is elastically deformed by~~  
~~the pull rod arrangement.~~
2. (Original) The window shade according to claim 1 wherein the lip is formed  
on an elastic profiled strip.
3. (Original) The window shade according to claim 1 wherein the guide rail is  
undercut in such a way that it forms a guide groove extending in the longitudinal direction  
that is accessible from the outside through a continuous slit extending in the longitudinal  
direction and wherein the clearance of the slit is less than the width of the guide groove  
measured in the same direction.
4. (Original) The window shade according to claim 1 wherein the guide groove  
has a circular cross section or a square cross section.
5. (Original) The window shade according to claim 1 wherein the guide rail  
includes a fastening flange that extends over substantially the entire length of the guide rail.
6. (Original) The window shade according to claim 1 wherein the guide rail is  
made from an extruded profiled element.

7. (Original) The window shade according to claim 1 wherein the guide rail includes a holding arrangement for fastening the elastic lip in a positive manner.

8. (Original) The window shade according to claim 7 wherein the holding arrangement for fastening the elastic lip comprises an undercut groove.

9. (Original) The window shade according to claim 1 wherein the lip has a corresponding fastening arrangement for connecting the lip positively with the guide rail.

10. (Original) The window shade according to claim 1 wherein the guide rail includes a flange for receiving a portion of a lateral trim of a motor vehicle.

11. (Original) The window shade according to claim 1 wherein two lips are provided.

12. (Currently Amended) The window shade according to claim 1 wherein the two lips directly touch each other.

13. (Currently Amended) The window shade according to claim 1 wherein said pull rod arrangement is moveable in a slit in said guide rail, and the said lip is configured such that it covers the slit.

14. (Original) The window shade according to claim 1 wherein the length of the pull rod arrangement can be adjusted in a telescope-like manner.

15. (Original) The window shade according to claim 1 wherein the pull rod arrangement has a guide body on at least one end that works together with the guide rail.

16. (Currently Amended) The window shade according to claim 1 wherein the guide body rail is connected with the pull rod arrangement via a neck and wherein measured in the direction transverse to the a longitudinal extension of the guide rail the neck has a lesser diameter than the guide body.

17. (Currently Amended) The window shade according to claim 1 wherein the guide body rail has a circular or polygonal cross section.

18. (Currently Amended) The window shade according to claim 1 wherein the guide ~~body~~ rail has larger dimensions in the longitudinal direction than in the transverse direction such that the guide body cannot be rotated with respect to the guide rail.

19. (Original) The window shade according to claim 7 wherein the holding arrangement for fastening the elastic lip comprises a strip that has a T-shaped cross section